

pennsylvania

DEPARTMENT OF TRANSPORTATION BUREAU OF MAINTENANCE AND OPERATIONS

Pilot car Must Keep Certificate 10/22/14 of Insurance in vehicle. 67 Po. Code 179.10 General Conditione (13)

| Pilot Car | 2 Pilot Cars | Condition | Comments |
|-----------|--------------|---|--|
| X | | Vehicle or Combination greater than 90' long or greater than 15' of rear overhang | 179.10(13)(A) |
| X | | Greater than 13' Wide but less than 14' Wide and less than 120' long | Title 75 Chapter 4962(f2) |
| | x | Greater than 13' Wide and Greater than 120' long | Exceeds length and width parameters of 4962(f2) |
| x | | Greater than 13' Wide and operating on highways having two or more lanes which carry traffic in the same direction as the permitted load | Chapter 179.10(13)(b)(I) |
| | | Greater than 13' Wide and operating on highways having only one lane which carries | Chapter 179.10(13)(b)(II) |
| Х | | traffic in the same direction as the permitted load | Pilot car must be in front of the load |
| x | | Greater than 13' Wide and is accompanied by the State Police | Chapter 179.10(13) (B)(III) Pilot car must follow the load |
| 123 | × | Greater than 13' Wide and exceeds 14'6" high | Chapter 179.10 (B) & (C) lead pilot car must have height pole |
| x | | Less than or equal to 13' Wide and exceeds 14'6"high | 179.10(13)(C) Only lead pilot car w/height pole needed |
| 15 | x | When moving a mobile home or a modular housing unit and a modular housing undercarriage over 14' Wide | 4973(d) |
| x | | When overweight permit requires permitted vehicle to travel over bridges at reduced speeds | 179.10(D)(I) |
| | x | When overweight permit requires permitted vehicle to be the only vehicle on a bridge span that supports two directional traffic | 179.10(D)(II) |
| x | | When overweight permit requires permitted vehicle to be the only vehicle on a bridge span that supports traffic moving in only one direction | 179.10(D)(II) |
| | x | When overweight permit load requires permitted vehicle to occupy more than one lane while crossing a bridge that supports two directional traffic | 179.10(D)(II) |
| x | | When overweight permit requires permitted vehicle to occupy more than one lane while crossing a bridge that supports traffic moving in only one direction | 179.10(D)(II) |
| | x | When oversized permitted vehicle is traveling within an urban area during hours of darkness | 179.10(E) |
| x | | When permitted vehicle is not capable of maintaining at least 40mph on limited access highways within urbanized areas between 9am and 4pm | 179.10(E) |
| x | | When permitted vehicle is not capable of maintaining 40mph on limited access highways in nonurban areas | 179.10(F) |
| | | Pilot Car Placement | |
| | | When one pilot car due to length, weight or width is required, the pilot car will follow When a pilot car is required due to height, the pilot car will lead using a height pole When two pilot cars are required, One shall lead and one shall follow. | |